

TECHNICAL DATA SHEET

FIRE STOP PARTY WALL BATTS

FIRE-RATED PARTY WALL INSULATION

Product description and typical applications

Constructed from mineral wool technology, Fire Stop Party Wall Batts are designed to provide fire protection in party or separating wall constructions between adjacent tenancies. Fire Stop Party Wall Batts are installed between the top of a party wall and the roofing membrane (in Class 1 and 10 buildings) to provide excellent fire resistance at high temperatures. When installed correctly, Fire Stop Party Wall Batts can achieve a 2 hour CSIRO fire rating thereby preventing the transfer of fire into an adjoining occupancy.

All Fire Stop insulation must be installed as per the architectural specification or system specific test description. In a Class 1 and 10 building, Fire Stop Party Walls Batts should be being compression fitted (with a minimum of 15% compression) between the top of the fire rated party wall and the roofing membrane leaving no voids.

Physical characteristics

Nominal thickness mm	Width mm	Length mm	Density kg/m ³	Product code
100	168	1200	64	338005
50	200	1000	64	338006

Technical specifications

	Result	Test method
Thermal conductivity	0.035 W/mk	ASTM C518
Corrosion resistance	Non-corrosive, Type I, III	ASTM C655
Alkalinity	Ph 7.0 – 9.0; Less than 20ppm soluble chlorides	BS 3958 part 5 – 1969
Specification	Type IA, IB, II	ASTM C612
Combustibility	Rated Non-combustible as per NFPA Standard 220	ASTM E136
	Non-combustible	AS 1530.1:1994
Fire hazard properties	Ignitability: 0, Flame Spread: 0, Smoke Developed: 0, Heat Evolved 0	AS/NZS 1530.3:1999
Water vapour transmission	Unfaced, 50 perms as tested	ASTM E96
Moisture absorption	Less than 1% by volume	ASTM C1104

Green Star compliant

Fletcher Insulation avoids the use of Ozone Depleting Potential (ODP) substances in the composition of Mineral Wool Insulation products. This allows the incorporation of environmentally preferable insulation whilst also maintaining indoor air quality. The product's chemical composition and the manufacturing of this product does not contain nor produce ozone depleting substances such as CFC's, or HCFC's. Fire Stop Party Wall products do not contain asbestos.

Specification notes

The insulation material shall be Fletcher Insulation Fire Stop Party Wall Batts _____ x _____ x mm (specify width and thickness) with a nominal density of 64kg/m³.

© Fletcher Insulation Pty Limited 2016. Fletcher Insulation reserves the right to change product specifications without prior notification. Information in this publication and otherwise supplied to users as to the subject product is based on our general experience and is given in good faith, but because of the many particular factors which are outside our knowledge and control and affect the use of products, no warranty is given or is to be implied with respect to either such information or the product itself, in particular the suitability of the product for any particular purpose. The purchaser should independently determine the suitability of the product for the intended application. Unless otherwise stated all TM and [®] are trademarks and registered trademarks of Fletcher Insulation Pty Limited ABN 72 001 175 355.

RTDS4_Revision_2_Issue Date 27072017

Fletcher[®]
Insulation

Building Better, Together.